What is claimed is:

1. A heat-resistant magnesium alloy for casting, the magnesium alloy being good in terms of the castability and heat resistance, and comprising:

calcium (Ca) in an amount of from 1 to 15% by mass; aluminum (Al) in a summed amount of from 4 to 25% by mass with the amount of Ca; and

the balance being magnesium (Mg) and inevitable impurities when the entirety is taken as 100% by mass.

- 2. The heat-resistant magnesium alloy set forth in claim 1 further comprising manganese (Mn) in an amount of from 0.1 to 1% by mass.
- 3. The heat-resistant magnesium alloy set forth in claim 1, wherein a mass ratio of the Ca amount with respect to the Al amount, Ca/Al by mass, is 1 or more.
- 4. The heat-resistant magnesium alloy set forth in claim 1, wherein a solidification temperature width, a temperature difference between a liquidus temperature at which a molten metal starts solidifying and a solidus temperature at which the molten metal completes solidifying, is $110~\mathrm{C}$ or less.
- 5. The heat-resistant magnesium alloy set forth in claim 1 being free from a rare-earth element.

- 6. The heat-resistant magnesium alloy set forth in claim 1 whose average crystalline grain diameter indexing the structural roughness is 18 μ m or less.
- 7. A heat-resistant magnesium alloy cast product being good in terms of the heat resistance, and produced by a process comprising the steps of:

pouring a molten alloy into a mold, the molten alloy comprising the heat-resistance aluminum alloy set forth in claim 1; and solidifying the molten alloy by cooling it after the pouring step.

- 8. The heat-resistant magnesium alloy cast product set forth in claim 7 being free from a rare-earth element.
- 9. The heat-resistant magnesium alloy cast product set forth in claim 7 whose average crystalline grain diameter indexing the structural roughness is 18 μ m or less.